

Information

Hubs and Axles

Brake Assemblies

Suspensions & Fasteners

Tires & Wheels

Couplers, Jacks & Winches

Hitches & Towing Accessories

Body Components

Boat Trailer Parts

Lights & Electrical

Locks & Cargo Control

Brake Actuating Systems

Switches



2,000# Dexter Sprung Axles Assembly

Made to Order

Overhang = (Hub Face - Spring Center)

Features and Options	
Tubing	1-3/4" OD - .180 Wall (straight only) 2-3/8" OD - .156 Wall (drop only)
Bearings	#44649 Inner & Outer
Hub	4 Lug on 4.0" 5 Lug on 4.5" (5.5" dia. for 8" - 12" wheels) 5 Lug on 4.5" (6.5" dia. for 12" - 15" wheels)
Brake	7" x 1-1/4" Electric 7" x 1-3/4" Hydraulic
Suspension	1-3/4" Double Eye Springs 1-3/4" Slipper Springs Hanger Kit
Lubrication	Grease or EZ-Lube

Axle Type	Min.	Max.
Straight	11.50"	15.25"
4" Drop	15.25"	18.00"



3,500# Dexter Sprung Axles Assembly

Made to Order

Overhang = (Hub Face - Spring Center)

Features and Options	
Tubing	2-3/8" OD - .180 Wall (standard) 3" OD - .191 Wall (optional)
Bearings	#68149 Inner & #44649 Outer
Hub	5 Lug on 4.5", 4.75", 5.0" or 5.5" 6 Lug on 5.5"
Brake	10" x 2-1/4" Electric 10" x 2-1/4" Hydraulic* <i>*single servo, duo servo or free backing</i> Disc Brake
Suspension	1-3/4" Double Eye Springs 1-3/4" Slipper Springs Hanger Kit
Lubrication	Grease or EZ-Lube Nev-R-Lube (655 Straight Axle Only)

Axle Type	Min.	Max.
Straight	11.25"	18.00"
Straight (3" Tube)	11.25"	23.00"
4" Drop	14.00"	18.00"
4" Drop (3" Tube)	14.00"	23.00"
6" Drop	15.75"	18.00"

These axles available on request